

Ferrule INOX Talurit®

Product information



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing [... Read more](#)

Material: Stainless steel, AISI 316.

Note: See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

Ferrule INOX Talurit®

Technical data

Part Code	Ferrule size mm
10.04INOX01	1
10.04INOX015	1.5
10.04INOX02	2
10.04INOX025	2.5
10.04INOX03	3
10.04INOX035	3.5
10.04INOX04	4
10.04INOX045	4.5
10.04INOX05	5
10.04INOX06	6
10.04INOX07	7
10.04INOX08	8
10.04INOX09	9
10.04INOX10	10
10.04INOX11	11
10.04INOX12	12
10.04INOX13	13
10.04INOX14	14
10.04INOX16	16
10.04INOX18	18
10.04INOX20	20
10.04INOX22	22
10.04INOX24	24
10.04INOX26	26
10.04INOX28	28
10.04INOX30	30
-	32