

Ferrule STS Talurit®

Product information



Ferrule for splicing of steel wire rope.

Typically carbon steel ferrules are used when corrosion, higher temperature and special dragging applications are used. This system is also an alternative to the flemish eye, this is due to the fact that you have all the benefits as above but the simplicity of a straight turnback system.

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. It is far more efficient than all other swaging methods on the market.

[... Read more](#)

Material: Carbon steel

Marking: According to standard

Standard: EN 13411-3

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Ferrule STS Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
10.03STS05	5	22
10.03STS06	6	26
10.03STS07	7	31
10.03STS08	8	34
10.03STS09	9	39
10.03STS10	10	43
10.03STS11	11	52
10.03STS12	12	57
10.03STS13	13	60
10.03STS14	14	69
10.03STS16	16	78
10.03STS17	17	62
10.03STS18	18	65
10.03STS20	20	73
10.03STS22	22	80
10.03STS24	24	87
10.03STS28	28	102
10.03STS30	30	109
10.03STS34	34	124
10.03STS38	38	139
10.03STS42	42	153
10.03STS44	44	161
10.03STS48	48	175
10.03STS52	52	190
10.03STS56	56	204
10.03STS60	60	219
10.03STS64	64	234
10.03STS68	68	248
10.03STS72	72	263
10.03STS76	76	278
10.03STS84	84	307

Ferrule STS Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
10.03STS90	90	329