

Ferrule UM Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

... [Read more](#)

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except rope type range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Ferrule UM Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
10.01UM09	9	36
10.01UM10	10	41
10.01UM11	11	45
10.01UM12	12	50
10.01UM13	13	55
10.01UM14	14	59
10.01UM16	16	64
10.01UM18	18	73
10.01UM20	20	82
10.01UM22	22	91
10.01UM24	24	100
10.01UM26	26	109
10.01UM28	28	118
10.01UM30	30	127
10.01UM32	32	136
10.01UM34	34	146
10.01UM36	36	155
10.01UM38	38	164
10.01UM40	40	173
10.01UM42	42	182
10.01UM44	44	191
10.01UM46	46	200
10.01UM50	50	209
10.01UM54	54	228
10.01UM58	58	246
10.01UM62	62	264
10.01UM66	66	282
10.01UM70	70	300
10.01UM74	74	319
10.01UM78	78	337
10.01UM82	82	355

Ferrule UM Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
10.01UM90	90	391